

Page 1 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision Date: 8/3/2023 1. PRODUCT & COMPANY IDENTIFICATION 1.1 Product Name: DEOXIT® GREASE, TYPE L260CP (COPPER PARTICLES) 12 Chemical Name: DeoxIT® Grease L260Cp PART NOS: Part No. L260-C2G (2 grams); Part No. L260-C1 (28 g); 1.3 Synonyms: Part No. L260-C8 (226 g); Part No. L260-C8J (224 g); Part No. L260-C8TP (226 g) Part No. L260-C360 (3.6 Kg); Part No. L260-C35 (15.9 Kg); DeoxIT® Grease Type L260CP 1.4 Trade Names: 1.5 Product Uses & Restrictions: Lubricant 1.6 Distributor's Name: CAIG Laboratories, Inc. 1.7 Distributor's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN205206) Business Phone / Fax: 1.9 +1 (800) 224-4123 2. HAZARDS IDENTIFICATION This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the 2.1 Hazard Identification: classification criteria of WHSR and ADG Code (Australia). DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES EYE IRRITATION. Classification: Asp. Tox. 1; Eye Irrit. 2B Label Elements: 22 Hazard Statements (H): H304 - May be fatal if swallowed and enters airways. H320 - Causes eye irritation Precautionary Statements (P): P264 - Wash thoroughly after handling. P280 - Wear protective gloves and eye/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 – Do NOT induce vomiting. P321 – Refer to section 4 of this Safety Data Sheet (First Aid). P305+P351+P338 - IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P405 - Store locked up. P501 - Dispose of contents/container through licensed treatment, storage, or disposal facility. 2.3 Other Warnings KEEP LOCKED UP AND OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-CHEMICAL NAME(S) CAS No. RTECS No. EINECS No. STEL TWA PEAK PEL STEL IDLH OTHER STE 60-100 NF 100 NA RESP MIST LITHIUM GREASE LUBRICATING NA NA NA 5 10 10 NF NF BASE OIL Asp. Tox. 1 CONTAINS ONE OR MORE OF THE FOLLOWING INGREDIENTS: DISTILLATES (PETROLEUM), 64742-65-0 SE7500000 265-169-7 1-60 5 10 NF NF NF 100 10 NA RESP MIST SOLVENT-DEWAXED HEAVY Carc 1B; H350; REACH Reg. No. 01-1119471299-27 PARAFFINIC* 64742-01-4 265-101-6 10 NF NF RESIDUAL OILS (PETROLIUM) NA 1-25 5 NF 5 10 NA RESP MIST SOLVENT-REFINED* Carc 1B; H350; REACH Reg. No. 01-211948707-21 DISTILLATES (PETROLEUM). 64741-88-4 PY8040500 265-090-8 1-25 5 10 NF NF NF 10 NA RESP MIST SOLVENT-REFINED HEAVY Carc 1B; H350; REACH Reg. No. 01-2119488706-23 PARAFFINIC* 68649-42-3 NA 272-028-3 1-.25 NA NA NF NF NF NA NA NA ZINC ALKYL DITHIOPHOSPHATE Skin Irrit. 2; Eye Irrit 2; H315, H319 REACH Reg. No. 01-211949365-27; 01-2119657973-23; Skin Irrit. 2; Eye Dam. 1; Aq. Chronic 2; H315, H318, H411 NA NA NF NF NF NA NA NA TRADE SECRET 0-10 DeoxIT® PROPRIFTARY MIX Eye Irrit. 2B; H320; REACH Reg. No. Non-Hazardous/Proprietary 7440-50-8 GL5325000 231-159-6 <9.0 0.2 NA NF 0.2 NF 0.1 NA COPPER *Contains < 3% DMSO 4. FIRST AID MEASURES If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk 4.1 First Aid: Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm Eyes: water for at least 15 minutes lifting upper and lower lids, occasionally. Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at Skin: least 15 minutes. Remove victim to fresh air at once. If breathing difficult, administer oxygen. If breathing stops give Inhalation:

artificial respiration. Keep person warm, quiet and get medical attention.



Page 2 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 4.2 SDS Revision Date: 8/3/2023 4. FIRST AID MEASURES - cont'd If product is swallowed, may cause nausea, temporary gastrointestinal irritation. vomiting and/or diarrhea. 42 Effects of Exposure: Ingestion: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: None expected. 4.3 Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Eyes: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals. 4.4 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 None reported by the manufacturer. 4.6 Target Organs: Eyes, Skin 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the HEALTH 1 Aggravated by Exposure: target organs (eyes, skin). **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 В PROTECTIVE EQUIPMENT **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO_X). Extinguishing Methods: 52 Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink, or smoke while handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk covered. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Container is not designed to contain pressure. Don not use pressure to empty container or it may rupture with explosive force. Normal shelf-life: 2-3 years. 7.3 Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. Empty containers may contain product residues. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.



Page 3 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 4.2

SDS Revision Date: 8/3/2023

		8. EXPOSURE CONTROL	. <u></u>	FLNS	DINA	L PN) I E C		<u> </u>		
	Exposure Limits:		AC	GIH		NOHSC			OSHA	1	OTHER
ŀ	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
		LITHIUM GREASE LUBRICATING BASE OIL	5	10	NF	NF	NF	100	10	NA	RESP MIST
		DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	100	10	NA	RESP MIST
		RESIDUAL OILS (PETROLIUM) SOLVENT- REFINED	5	10	NF	NF	NF	5	10	NA	RESP MIST
		DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	5	10	NA	RESP MIST
	/entilation & Engineering Controls:	When working with large quantities of prototal that an eyewash station, sink or washbase							xhaust v	entilation	on, fans). Ens
8.3 F	Respiratory Protection:	necessary, use only respiratory protection	No special respiratory protection is required under typical circumstances of use or handling. If lecessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR 1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.								
8.4 E	Eye Protection:	Vear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; off lenses may absorb and concentrate irritants.									
8.5 H	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber or impervious plastic gloves.									
8.6 E	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									
		9. PHYSICAL & CI	HEMI	CAL	PRO	<u> PERII</u>	<u>ES</u>				
	Appearance:	Amber/copper grease									
	Odor:	Ethereal / hydrocarbon odor									
	Odor Threshold: bH:	NA NA									
	Melting Point/Freezing Point:	NA NA									
	nitial Boiling Point/Boiling	NA									
F	Range:	>240 °C (464 °F)									
	Flashpoint:	> 244 °C (471 °F) COC (Cleveland Oper	ı Cup)								
	Jpper/Lower Flammability imits:	NA									
	/apor Pressure:	<0.01 mmHg									
9.10	/apor Density:	NA									
9.11 F	Relative Density:	0.72									
9.12	Solubility:	Insoluble									
9.13 F	Partition Coefficient (log Pow):	NA									
9.14 A	Autoignition Temperature:	NA									
9.15	Decomposition Temperature:	NA									
0.16	/iscosity:	5.4-7.5 cSt									
0.17	Other Information:	NA									
											•
		10. STABILI	TY &	REA	CTIVI	TY					
10.1	Stability:	This product is stable.									
F	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (S	SO ₂). Li	beration	of gas n	ny result i	in dange	erous pr	essure.		
	Hazardous Polymerization:	Will not occur.									
	Conditions to Avoid:	Excessive heat, and incompatible materi									
10.5 I	ncompatible Substances:	Avoid extreme heat and ignition sources	Store	NAMON fro	m ovidiz	orc					



Page 4 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision Date: 8/3/2023 11. TOXICOLOGICAL INFORMATION Absorption: YES 11.1 Routes of Entry: Inhalation: YES Ingestion: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis) 11.5 Suspected Carcinogen No. Less than 3% (w/w%) DMSO, complex oil-derived substances in part 3 of this SDS 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. This product is not reported to produce mutagenic effects in humans. This product contains Alkyl Dithiophosphates Mutagenicity: (ZDDPs). Several ZDDPs have been reported to have weak mutagenic activity in cultured mammalian cells but only at concentrations that were toxic. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11 7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices: NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: There is no specific data available for this product. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: This material should be kept out of sewage and drainage systems and all bodies of water. Releases of large volumes of this product are expected to be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste Disposal Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. Special Considerations 13.2 NA 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): 14.1 **NOT REGULATED** IATA (AIR) 14 2 **NOT REGULATED** IMDG (OCN): 14 3 **NOT REGULATED** TDGR (Canadian GND): 14.4 **NOT REGULATED** 14.5 ADR/RID (EU): **NOT REGULATED** 14.6 SCT (MEXICO): **NOT REGULATED** 14 7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION SARA Reporting 15.1 This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory 15.4 CERCLA Reportable Quantity NA 15.5 Other Federal Requirements: This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-know Act of 1986 and of CFR 372; 68649-42-3 Zinc Alkyl Dithiophosphate Other Canadian Regulations: 15.6 This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15.7 State Regulatory Information: No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings.ca.gov 15.8 Other Requirements: German Water Hazard Class: WGK 3 This product is found on the following inventory lists: Australia - AICS, China - IECSC, Europe - ELINCS/EINEC, Japan

- ENCS; Korea - KECI; New Zealand - NZIoC; {Philippines - PICCS; USA - TSCA



Page 5 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 4.2 SDS Revision Date: 8/3/2023 16. OTHER INFORMATION DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES EYE IRRITATION. Other Information: Obtain instructions before use. Do not handle until all safety precautions have been read and understood before use Wash thoroughly after handling. Wear protective gloves and eye/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Refer to section 4 of this Safety Data Sheet (First Aid). IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If eye irritation persists: Get medical advice/attention. Store locked up. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other 16.3 Disclaimer: government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: 16.4 CAIG Laboratories. Inc. 12200 Thatcher Court Powav. CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA

Training & Consulting

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com



Page 6 of 6 SDS-E-L260CP

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision Date: 8/3/2023

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number					
RTECS No. Registry of Toxic Effects of Chemical Substances Number					
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number				

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists		
IDLH	IDLH Immediately Dangerous to Life and Health		
NOHSC	National Occupational Health and Safety Commission (Australia)		
OSHA	U.S. Occupational Safety and Health Administration		
PEL Permissible Exposure Limit			
STEL	Short Term Exposure Limit		
TLV Threshold Limit Value			
TWA Time Weighted Average			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1	1 Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4 Extreme Hazard			

HEALTH FLAMMABILITY PHYSICAL HAZARDS PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Е			
F			















Cy



Full Face Respirator





ð Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:					
Autoignition Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL Lower Explosive Limit - lowest percent of vapor in air, by volum explode or ignite in the presence of an ignition source						
UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that vexplode or ignite in the presence of an ignition source						

HAZARD RATINGS:

Minimal Hazard		FLAMMABILITY					
1 Slight Hazard		\					
2 Moderate Hazard		REACTIVITY					
3 Severe Hazard							
4 Extreme Hazard							
ACD Acidic							
ALK Alkaline							
COR	Corrosive	─ / ▼ ₩ >					
₩ Use No Water		HEALTH 🔪					
ОХ	Oxidizer	SPECIAL					
TREFOIL	Radioactive	PRECAUTIONS					

TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TDio	Lowest dose to cause a symptom			
TCLo	Lowest concentration to cause a symptom			
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TCo, LCio, & LCo				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log Kow or log Koc	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System		
DOT	DOT U.S. Department of Transportation		
TC	Transport Canada		
EPA	U.S. Environmental Protection Agency		
DSL	DSL Canadian Domestic Substance List		
NDSL	Canadian Non-Domestic Substance List		
PSL	Canadian Priority Substances List		
TSCA	U.S. Toxic Substance Control Act		
EU	EU European Union (European Union Directive 67/548/EEC)		
WGK	WGK Wassergefährdungsklassen (German Water Hazard Class)		

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(3)	(3)		(T)	®		Ä
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond					*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment