

Page 1 of 6 SDS-E-L260DCP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

SDS Revision Date: 8/3/2023

	[PRODUC											
1.1	Product Name:	DEOXIT®	GREAS	E, TYPE I	L260D	CP (COP	PEF	RPA	ART	CLE	ES)		
1.2	Chemical Name:	NA												
1.3	Synonyms:		ase L260DCp -DC2G (2 grar		art Na I O	60 DC	1 (20 ~	۸.		De	ut Nia	L260-E) (2)	nne «\.
			i-DC2G (2 grai i-DC8TP (226 g		art No. L2 Part No. L2									:26 g), (15.9 Kg);
1.4	Trade Names:				art No. Lz	200-00	,500 (5	.o rvg)	,	1 6	iit ivo.	LZUU-L	7033 ((13.9 Kg),
1.5	Product Uses & Restrictions:		DeoxIT® Grease Type L260DCp Lubricant for mechanical and electrical applications											
1.6	Distributor's Name:	CAIG Laboratories, Inc.												
1.7	Distributor's Address:	12200 Thatcher Court, Poway, CA 92064-6876 USA												
1.8	Emergency Phone:	CHEMTRE	C: +1 (703)	527-3887 /	+1 (800)) 424	-9300) (CC	N20	5206)			
1.9	Business Phone / Fax:	+1 (800) 224-4			- (,								
			2 LI/	AZARDS	IDENT	IEIC	A TIC) NI						
2.1	Hazard Identification:	This product							t ac	DANG	EDOL	IS GO	ODS	according to the
2.1	riazara racrianoatori.													oil contains < 3%
		(w/w%) DMSC					, ao (, te	otrana	.,	io ing	iny 1011	1104 1111	inorai	on containe + 670
		DANGER! MA				ENTE	RS AIF	RWAY	S.					
2.2	Label Elements:	Hazard Staten												
		Precautionary												_
		ON SKIN - W												
		POISON CEN of this Safety	Data Shoot (/pnysician. Po	331 – Do i 05±0351	NOT IN	duce v	omitino	j. P32	21 – K	eter to	Sectio	n 4	
		water for seve												
		P405 – Store												
		or disposal fac	ility.	•								-		
2.3	Other Warnings:	KEEP LOCKE	D UP AND O	UT OF REACH	OF CHIL	DREN	l							
		3. CC	MPOSIT	<u>ION & INC</u>	GRED	ENT	INF	ORI	<u>TAN</u>	ION				
								ı			IMITS II	N AIR (m	g/m³)	Т
							GIH om		NOHS(;		OSHA		
						PI	JIII	ES-	ES-	ES-		Ppin		-
	CAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK		STEL	IDLH	OTHER
LITHIU	JM GREASE LUBRICATING	NA	NA	NA	60-100	NA	NA	NF	NF	NF	NA	NA	NA	
	AINS ONE OR MORE OF TH	E FOLLOWING	INGREDIENTS:											
	LATES (PETROLEUM),	64742-65-0	SE7500000	265-169-7	NA	5	10	NF	NF	NF	100	10	NA	RESP MIST
SOLV	ENT-DEWAXED HEAVY		No. 01-21194712	1										•
	FFINIC		1		Tala	-	40	NE	NE	NE	I -	40		DEODAMOT
	OUAL OILS (PETROLIUM) ENT-REFINED	64742-01-4	NA No. 01-21194887	265-101-6	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
	LATES (PETROLEUM),	64741-88-4	PY8040500	265-090-8	NA	5	10	NF	NF	NF	5	10	NA	RESP MIST
SOLV	ENT-DEWAXED HEAVY		No. 01-21194887	1				1			<u>. </u>			,
PARA	FFINIC	ŭ	1		Tara						1	1		
ZINC	ALKYLDITHIOPHOSPHATE	68649-42-3	NA Skin Irrit. 2; Eye I	272-028-3	NA onic 2: H31	NA 5 H318	NA H//11	NF	NF	NF	NA	NA	NA	
	_	TRADE SECR		Daill. 1, Aq. Chr	NA	5, H318 NA	NA	NF	NF	NF	NA	NA	NA	
DeoxIT® PROPRIETARY MIX REACH Reg. No. Non-Hazardous/Proprietary						1								
CODD		7440-50-8	GL5325000	231-159-6	<9.0	0.2	NA	NF	0.2	NF	0.1	NA	100	
COPP	EK													
<u> </u>														
				FIRST A										
4.1	First Aid:													of water or milk
														ater or milk to an
														mber. Provide an ostance that was
			estimate of th swallowed.	ie uiiie at wh	ion ine m	ıatenal	was I	ngeste	an an	u ine	amoul	ונ 10 נו	ie sul	ustance that was
				not likely: howe	ever, if pro	duct a	ets in f	he eve	s. flus	sh with	copio	us amo	ounts o	of lukewarm water
			for at least 15								1-1-2-1			
1														
				hly with soap a	and water.	In cas	se of co	ontact,	imme	ediatel	y flush	skin w	ith ple	nty of water for at
			least 15 minute	es.									·	•
		Inhalation:		es. n to fresh air at	once. If	breathii	ng diffi	cult, ad	dminis	ter ox	ygen.		·	•



Page 2 of 6 SDS-E-L260DCP

ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 8/3/2023 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, temporary gastrointestinal irritation. vomiting and/or diarrhea. Eyes: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Inhalation: None expected. 4.3 Symptoms of Overexposure: Nausea, intestinal discomfort, vomiting and/or diarrhea. Ingestion: Overexposure in eyes may cause redness, itching and watering. Eyes: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Frostbite Skin: like symptoms. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some 44 Acute Health Effects: Non-irritating when used as directed. Moderate irritation to eves and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 None reported by the manufacturer. 4.6 Target Organs: Eyes, Skin 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin). **FLAMMABILITY** 0 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: This product is not flammable. However, if involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO,CO_x). 5.2 Extinguishing Methods: Water, Foam, CO₂, Dry Chemical. Use water spray to cool unopened containers. 5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Avoid spraying water directly into storage containers because of danger of boil-over. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer product to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Do not eat, drink, or smoke while handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk covered. Wash unintentional residues with soap and warm water. 7.2 Storage & Handling: Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Container is not designed to contain pressure. Don not use pressure to empty container or it may rupture with explosive force. Normal shelf-life: 2-3 years 7.3 Special Precautions: Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. Empty containers may contain product residues. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.



Page 3 of 6 SDS-E-L260DCP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

SDS Revision Date: 8/3/2023

		8. EXPOSURE CON	TRO	LS &	PERS	ONAL	PROTE	CTI	ON		
8.1	Exposure Limits:			GIH		NOHSC			OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	100	10	NA	RESP MIST
		RESIDUAL OILS (PETROLIUM) SOLVENT-REFINED	5	10	NF	NF	NF	5	10	NA	RESP MIST
		DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	5	10	NF	NF	NF	5	10	NA	RESP MIST
		COPPER	0.2	NA	NF	NF	NF	0.1	NA	100	FUME
8.2	Ventilation & Engineering Controls:	When working with large quantit that an eyewash station, sink or							al exhau	ıst vent	lation, fans). Ens
8.3	Respiratory Protection:	No special respiratory protection necessary, use only respiratory §1910.134, or applicable U.S. provinces, E.C. member states,	/ proted	ction au regulati	thorized p	er U.S. C	SHA's req	uireme	nt in 29	9 CFR	
8.4	Eye Protection:	Wear protective eyewear (e.g., product. Always use protective special hazard; soft lenses may	e eyew	ear whe	n cleanin	g spills or					
8.5	Hand Protection:	special hazard; soft lenses may absorb and concentrate irritants. None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber or impervious plastic gloves.									
8.6	Body Protection:	No apron required when hand gallon), eye wash stations and activities involving large quantit and water.	deluge	e showe	ers should	be availa	ble. Upon	comp	letion o	f work	
		and water.									
		9. PHYSICAI	_ & C	HEM	IICAL I	PROPE	RTIES				
9.1	Appearance:	1	_ & C	HEM	IICAL I	PROPE	RTIES				
	Appearance: Odor:	9. PHYSICAI	_ & C	HEM	IICAL I	PROPE	RTIES				
9.2		9. PHYSICAI Amber / copper	_ & C	HEM	IICAL I	PROPE	RTIES				
9.2 9.3	Odor:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor	_ & C	HEM	IICAL I	PROPE	RTIES				
9.2 9.3 9.4	Odor: Odor Threshold:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA	_ & C	CHEM	IICAL I	PROPE	RTIES				
9.2 9.3 9.4 9.5	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA	_ & C	CHEM	IICAL I	PROPE	RTIES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA NA >240 °C (464 °F)			IICAL I	PROPE	RTIES				
9.2 9.3 9.4 9.5 9.6	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA			IICAL I	PROPE	RTIES				
9.2 9.3 9.4 9.5 9.6 9.7	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelation)			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F)			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.9 9.10 9.11 9.12 9.13	Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow):	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.14 9.15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.11 9.12 9.13 9.14 9.15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA S.4-7.5 cSt			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.11 9.11 9.13 9.15 9.16	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA			IICAL I	PROPE	ERTIES				
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.11 9.12 9.13 9.14 9.15	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA S.4-7.5 cSt	and Ope	en Cup)							
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.14 9.15 9.16	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA NA NA NA NA N	and Ope	en Cup)							
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition Products:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA 10. ST	and Ope	en Cup)	& REAC	CTIVIT	Y	ngerou	s pressi	ure.	
9.7 9.8 9.9 9.10 9.11 9.12 9.13 9.14 9.15 9.16 9.17 10.1 10.2	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition Products: Hazardous Polymerization:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevelate) NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA NA This product is stable. Oxides of carbon (CO, CO ₂) and will not occur.	ABIL	en Cup)	& REAC	CTIVIT	Y	ngerou	s pressi	ure.	
9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 9.10 9.12 9.13 9.14 9.15 9.16 9.17	Odor: Odor: Odor Threshold: pH: Melting Point/Freezing Point: Initial Boiling Point/Boiling Range: Flashpoint: Upper/Lower Flammability Limits: Vapor Pressure: Vapor Density: Relative Density: Solubility: Partition Coefficient (log Pow): Autoignition Temperature: Decomposition Temperature: Viscosity: Other Information: Stability: Hazardous Decomposition Products:	9. PHYSICAI Amber / copper Ethereal / hydrocarbon odor NA NA NA >240 °C (464 °F) > 244 °C (471 °F) COC (Clevela NA < 0.01 mm Hg @ 20 °C (68 °F) NA 0.72 Insoluble NA NA NA NA This product is stable. Oxides of carbon (CO, CO ₂) and	ABIL d sulfur	en Cup) ITY 8 (SO ₂). L	k REAC	CTIVIT'	Y	ngerou	s pressi	ure.	



Other Requirements

NA

SAFETY DATA SHEET

Page 4 of 6 SDS-E-L260DCP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 8/3/2023 11. TOXICOLOGICAL INFORMATION Inhalation: YES Absorption: YES Ingestion: YES 11.1 Routes of Entry: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is 11 2 Toxicity Data: available for some of the components of the product and is not presented in this document 11.3 Acute Toxicity: Moderate irritation to eyes and skin near affected areas. 11.4 Chronic Toxicity: This material may aggravate any pre-existing skin condition (e.g., dermatitis). Suspected Carcinogen: 11.5 NO. The highly refined mineral oil contains < 3% (w/w%) DMSO extract, according to IP346. 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. This product contains Alkyl Dithiophosphates (ZDDPs). Several ZDDPs have been reported to have weak mutagenic activity in cultured mammalian cells but only at concentrations that were toxic. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.8 Biological Exposure Indices: NE Physician Recommendations: 11.9 Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability There is no specific data available for this product. 12.1 Effects on Plants & Animals: 12.2 There are no specific data available for this product. 12.3 Effects on Aquatic Life Ethanol: EC₅₀ (Daphnia magna (water flea), 48h): 7.7 - 11.2 mg/L; LC₅₀ (Pimephales promelas (fathead minnow), 96h) > 100 mg/L; Alkyl Dimethyl Benzyl Ammonium Chloride: LC50 (Morone saxatilis (Striped bass, 96h): 10.4 - 19.1 mg/L 13. DISPOSAL CONSIDERATIONS 13 1 Waste Disposal Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. Special Considerations: 13.2 NA 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED 14.2 IATA (AIR): NOT REGULATED 14.3 IMDG (OCN): NOT REGULATED 14.4 TDGR (Canadian GND): NOT REGULATED 14.5 ADR/RID (EU): NOT REGULATED SCT (MEXICO): 14.6 **NOT REGULATED** 14.7 ADGR (AUS): **NOT REGULATED** 15. REGULATORY INFORMATION This product contains the following chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-know Act of 1986 and of CFR 372; 68649-42-3 Zinc Alkyldithiophosphate 15.1 SARA Reporting Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 NA This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G, 15.5 Other Federal Requirements: (Cosmetics) 15.6 Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state 15.7 State Regulatory Information: criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Page 5 of 6 SDS-E-L260DCP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.0

SDS Revision Date: 8/3/2023

		16. OTHER INFORMATION					
16.1	Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. Avoid contact with the eyes. Wear protective gloves and eye protection. IF ON SKIN – Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Specific Treatment: refer to Section 4 of the Safety Data Sheet (First Aid). IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Store locked up. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN.					
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Ot government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAL Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; hower accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, provided. The information contained herein relates only to the specific product(s). If this product(s) is combined wother materials, all component properties must be considered. Data may be changed from time to time. Be sure consult the latest edition.					
16.4	Prepared for:	CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 Tel: +1 (800) CAIG-123 (244-4123) Fax: +1 (858) 486-8398 fax http://www.caig.com/					
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com					



Page 6 of 6 SDS-E-L260DCP

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 8/3/2023

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		



PERSONAL PROTECTION RATINGS:

Α			
В			
С	ELA	THE STATE OF THE S	
D		H.	
Е	ELA		
F		H.	







Dust Respirator

ð Dust & Vapor Half-Mask Respirator **Full Face** Airline Hood/Mask Respirator or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:				
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	\
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	/ \ \ \
W	Use No Water	HEALTH 🔪
ОХ	Oxidizer	SPECIAL
TREFOIL	Radioactive	PRECAUTIONS

TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TDio	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	J.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	®	(2)	(X)	\odot	(49)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond	A PARTIES AND A		\Diamond		***
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment